



MEDITRAN SAE 30, 40, 50

MEDITRAN Series are a moderate duty diesel oil designed for non turbocharged diesel engine which require API CD lubricant.

MEDITRAN Series adalah pelumas mesin diesel tugas medium yang didesain untuk mesin diesel tipe non-turbocharged yang mensyaratkan pelumas dengan tingkatan mutu API CD.

TYPICAL CHARACTERISTICS				
Characteristics	Test Method	MEDITRAN 30	MEDITRAN 40	MEDITRAN 50
SAE Viscosity Grade		30	40	50
Density at 15 °C, kg/l	ASTM D - 4052	0.8794	0.8916	0.8949
Kinematic Viscosity at 40 °C, cSt	ASTM D - 445	89.34	130.1	194.7
	ASTM D - 445	10.51	13.46	17.48
Viscosity Index	ASTM D - 2270	100	98	96
ASTM Colour	ASTM D - 1500	L 3.0	L 3.0	3.0
Flash Point °C	ASTM D - 92	252	254	268
Pour Point, °C	ASTM D - 5950	-9	-9	-9
Total Base Number, mg KOH/g	ASTM D - 2896	4.72	4.62	4.79

PERFORMANCE LEVELS

MEDITRAN Series engine oils meet the performance level of API CD.

TINGKATAN MUTU

MEDITRAN Series memenuhi persyaratan API CD.